


СВЕРЛЕНИЕ Сверла со сменными пластинами

Сверла CoroDrill® 880 со сменными пластинами

Хвостовик Coromant Capto®

Дюймовое исполнение

TCHAL .000
TCHAU .016



4 x DC

CZC _{MS}	DC	DC"	ADJLX	ADJLX"	Код заказа	Размеры, мм, дюйм						
						DCON	LU	LU"	LF	LF"	KAPR	
01	C4	12.70	.500	0.25	.009	A880-D0500C4-04	40.00	53.3	2.100	83.03	3.269	79°
	C5	12.70	.500	0.25	.009	A880-D0500C5-04	50.00	53.3	2.100	83.03	3.269	79°
	C6	12.70	.500	0.25	.009	A880-D0500C6-04	63.00	53.3	2.100	85.03	3.347	79°
	C4	13.48	.531	0.25	.009	A880-D0531C4-04	40.00	56.6	2.230	86.68	3.412	79°
	C5	13.48	.531	0.25	.009	A880-D0531C5-04	50.00	56.6	2.230	86.68	3.412	79°
	C6	13.48	.531	0.25	.009	A880-D0531C6-04	63.00	56.6	2.230	88.64	3.489	79°
02	C4	14.27	.562	0.45	.017	A880-D0562C4-04	40.00	59.9	2.360	90.31	3.555	88°
	C5	14.27	.562	0.45	.017	A880-D0562C5-04	50.00	59.9	2.360	90.31	3.555	88°
	C6	14.27	.562	0.45	.017	A880-D0562C6-04	63.00	59.9	2.360	92.31	3.634	88°
	C4	15.87	.625	0.25	.009	A880-D0625C4-04	40.00	66.7	2.628	97.96	3.857	88°
	C5	15.87	.625	0.25	.009	A880-D0625C5-04	50.00	66.7	2.628	97.96	3.857	88°
	C6	15.87	.625	0.25	.009	A880-D0625C6-04	63.00	66.7	2.628	99.97	3.935	88°
03	C4	16.66	.656	0.58	.022	A880-D0656C4-04	40.00	69.9	2.755	101.29	3.987	88°
	C5	16.66	.656	0.58	.022	A880-D0656C5-04	50.00	69.9	2.755	101.29	3.987	88°
	C6	16.66	.656	0.58	.022	A880-D0656C6-04	63.00	69.9	2.755	103.27	4.065	88°
	C4	17.44	.687	0.51	.020	A880-D0687C4-04	40.00	72.9	2.871	104.93	4.131	88°
	C5	17.44	.687	0.51	.020	A880-D0687C5-04	50.00	72.9	2.871	104.93	4.131	88°
	C6	17.44	.687	0.51	.020	A880-D0687C6-04	63.00	72.9	2.871	106.94	4.210	88°
	C4	19.05	.750	0.25	.009	A880-D0750C4-04	40.00	79.6	3.135	112.59	4.432	88°
	C5	19.05	.750	0.25	.009	A880-D0750C5-04	50.00	79.6	3.135	112.59	4.432	88°
	C6	19.05	.750	0.25	.009	A880-D0750C6-04	63.00	79.6	3.135	114.60	4.512	88°
04	C4	20.62	.812	0.80	.031	A880-D0812C4-04	40.00	86.2	3.394	119.24	4.694	88°
	C5	20.62	.812	0.80	.031	A880-D0812C5-04	50.00	86.2	3.394	119.24	4.694	88°
	C6	20.62	.812	0.80	.031	A880-D0812C6-04	63.00	86.2	3.394	121.25	4.773	88°
	C4	22.22	.875	0.58	.022	A880-D0875C4-04	40.00	92.2	3.631	126.61	4.984	88°
	C5	22.22	.875	0.58	.022	A880-D0875C5-04	50.00	92.2	3.631	126.61	4.984	88°
	C6	22.22	.875	0.58	.022	A880-D0875C6-04	63.00	92.2	3.631	128.61	5.063	88°
	C4	23.79	.937	0.35	.013	A880-D0937C4-04	40.00	98.7	3.888	133.31	5.248	88°
	C5	23.79	.937	0.35	.013	A880-D0937C5-04	50.00	98.7	3.888	133.31	5.248	88°
	C6	23.79	.937	0.35	.013	A880-D0937C6-04	63.00	98.7	3.888	135.31	5.327	88°
05	C4	25.40	1.000	0.95	.037	A880-D1000C4-04	40.00	105.4	4.150	141.02	5.552	88°
	C5	25.40	1.000	0.95	.037	A880-D1000C5-04	50.00	105.4	4.150	141.02	5.552	88°
	C6	25.40	1.000	0.95	.037	A880-D1000C6-04	63.00	105.4	4.150	143.02	5.630	88°
	C4	26.97	1.062	0.75	.029	A880-D1062C4-04	40.00	111.1	4.375	148.55	5.848	88°
	C5	26.97	1.062	0.75	.029	A880-D1062C5-04	50.00	111.1	4.375	148.55	5.848	88°
	C6	26.97	1.062	0.75	.029	A880-D1062C6-04	63.00	111.1	4.375	150.56	5.927	88°
	C4	28.57	1.125	0.50	.019	A880-D1125C4-04	40.00	117.7	4.635	156.31	6.154	88°
	C5	28.57	1.125	0.50	.019	A880-D1125C5-04	50.00	117.7	4.635	156.31	6.154	88°
	C6	28.57	1.125	0.50	.019	A880-D1125C6-04	63.00	117.7	4.635	158.31	6.232	88°

Расшифровку обозначений см. на стр. K3

